



FEATURES

- GP-exclusive design
- New body design provides higher resistance to overpressure
- Ventilation holes provide excellent insulation
- Ergonomic design offers a shock-resistant handguard
- Internal components permit easier trigger pull and operation

SPECIFICATIONS

Part Number	YG4000
Maximum Volume	10.5 GPM
Rated Pressure	4500 PSI
Maximum Pressure	5000 PSI
Maximum Temperature	320°F
Port Sizes: Inlet	3/8" NPT-F
Outlet	1/4" NPT-F
Dimensions	8.0" x 7.3" x 1.3"
Weight	1.7 lb.
Material	Stainless Steel, Brass, Plastic, Buna-N, Teflon

PARTS LIST

YG4000 Y30200067 SPRAY GUN, REAR, w/GP LOGO

No	Part No.	Description	Kit	Qty
	* YKITG4000	YG4000 Repair Kit		
	** Y30202924	YG4000 Housing Assembly		
1.	Y30202624	Plastic Housing Assembly	**	1
2.	Y16307700	Screw, 5 x 18mm	**	7
3.	Y30251731	Pin, 5 x 27, 5mm		1
4.	Y30250684	Trigger		1
5.	Y30067584	Striker		1
6.	Y30411531	Plug, M10 x 1		1
7.	Y10401800	Backup Ring, 7.5x3, 2x1, 2mm	*	1
8.	Y10316500	O-Ring, 2.62 x 2, 84mm	*	1
9.	Y30200751	SS Piston		1
10.	Y30151084	Safety Latch		1
11.	Y30200835	Outlet Tube, 1/4 NPT		1
12.	Y30200535	Brass Body		1
13.	Y30253435	Inlet Tube, 3/8 F NPT		1
14.	Y30201420	Seat Assembly		1
15.	Y14744310	SS Ball, 11/32"	*	1
16.	Y30200351	SS Spring		1
17.	Y10306001	O-Ring, 1.78 x 12, 42mm	*	1
18.	Y30200431	Spring Holder Plug		1

